



CHAPTER 10 – BREAKWATER® OUTLINE

Introduction

For Chapter 10 Breakwater®, we partnered with well-respected Southern California-based designer Katerina Tana. Katerina developed this stunning Breakwater collection inspired by her passions: the ocean, fine linen, and crisp, clean design.

Key Features

Chapter 10 Breakwater is a unique handcrafted gloss ceramic collection. The most striking of these is the Belgian linen texture, which is actually pressed into the wet clay prior to firing. Great care is taken by tile artisans to ensure that the linen effect is authentic.

- **Colors**
 - All field tiles, mosaics, and trims are offered in six stunning and vibrant colors, in a wonderful gloss finish: Breeze, Mist, Sail, Sand, Sea and Sunlight.
- **Field Tiles**
 - Field tiles are offered in three sizes: a 3" x 9" bar tile, a 3" x 3" field tile, and a 6" x 18" plank.
- **Mosaics**
 - This chapter features six hand assembled ceramic mosaics with a true linen texture in the aforementioned colors.
- **Decorative Tiles**
 - The popularity of the linen texture is closely followed by the beautiful 3" x 3" coral motif hand-pressed decorative tiles. These decorative tiles are also offered in all six colors.
- **Mouldings and Trims**
 - Breakwater also includes linen textured mouldings in 1" x 9" rail, 2" x 9" crown, and a 3^{3/4}" x 9" base.
 - If your design requires traditional bullnose pieces, they are available in 3" x 9" SBN and 3" x 3" DBN.

Application

Please reference the Application Chart for Chapter 10 on our website, JeffreyCourt.com, for more details on recommended applications.

Testing

Product specifications are listed on each product specific web page on JeffreyCourt.com. If available, testing results for applicable products: ceramic, glass, and porcelain, can be found on the back of the respective chapter catalog for easy reference.



Installation Tips

- **Blending and Shade Variation**
 - To achieve your desired look, Jeffrey Court recommends that you inspect and confirm the tile and layout prior to installation. Installation of tile constitutes acceptance.
- **Rating**
 - For specific item-by-item shade variation rating, please reference each product specific web page on JeffreyCourt.com.
- **Setting Materials, Sealers and Grouts**
 - A high-quality white thinset meeting ANSI 118.4 or 118.11 is recommended for best installation results. Always check with setting material manufacturer to ensure suitability of material in setting tiles. A grey mortar, or mastic or adhesives could stain or alter the color of the product.
 - As per the Tile Council of North America (TCNA): "For cementitious grout, joints smaller than 1/8" generally should only be grouted with unsanded grout, and joints of 1/8" and larger should only be grouted with sanded grout."
 - Grout color is part of the design process and considerations must be made. A grout choice closest to the color and hue of the tile being grouted can be considered the safest choice.
- **Cutting**
 - A professional grade wet saw outfitted with a high-quality diamond blade designed for cutting tiles is recommended. Always cut tiles with the face up.

Merchandising

The marketing and merchandising of this collection is supported by montage boards, touch boards, and A&D sample cards which aid in displaying the full product line. All of these point of purchase materials are accompanied by the Chapter 10 Breakwater catalog. Showroom installation and loose sample pieces can also be ordered at a discounted price.

Visit the Jeffrey Court website, JeffreyCourt.com, to gain inspiration on the design possibilities offered with Chapter 10 Breakwater.